

KEMET Part Number: PHE840MY6470MD14R13
(F840DH474M275ALD0JVBLK)

PHE840M/F840, Film, Metallized Polypropylene, Safety, 0.47 uF, 20%, 275 VAC (X2), 760 VDC, 105°C, Lead Spacing = 22.5mm



Dimensions

| | |
|-----------|-----------------|
| L | 26mm MAX |
| H | 16mm MAX |
| T | 8mm MAX |
| S | 22.5mm +/-0.4mm |
| LL | 13mm NOM |
| F | 0.8mm NOM |

Packaging Specifications

| | |
|-------------------|-----------|
| Packaging: | Bulk, Bag |
|-------------------|-----------|

General Information

| | |
|-------------------------|--|
| Series: | PHE840M/F840 |
| Dielectric: | Metallized Polypropylene |
| Style: | Radial |
| Features: | EMI Safety |
| RoHS: | Yes |
| Lead: | Wire Leads |
| Safety Class: | X2 |
| Qualifications: | ENEC, UL, cUL |
| AEC-Q200: | No |
| THB Performance: | No |
| Notes: | Not For New Design, Please Check Possible Alternative Parts (AltPart). |

Specifications

| | |
|-------------------------------|-----------------------|
| Capacitance: | 0.47 uF |
| Capacitance Tolerance: | 20% |
| Voltage AC: | 275 VAC (X2) |
| Voltage DC: | 760 VDC |
| Temperature Range: | -55/+105°C |
| Rated Temperature: | 105°C |
| Dissipation Factor: | 0.1% 1kHz, 0.4% 10kHz |
| Insulation Resistance: | 21.2766 GOhms |
| Max dV/dt: | 100 V/us |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)