

KEMET Part Number: MMK15683K630B06L4BULK
(F601BL683K630C)

KEMET

a YAGEO company

MMK/F601, Film, Metallized Polyester, General Purpose, 0.068 uF, 10%, 630 VDC, 85°C, Lead Spacing = 15mm



General Information

| | |
|--------------------|--|
| Series: | MMK/F601 |
| Dielectric: | Metallized Polyester |
| Style: | Radial |
| Features: | DC Multipurpose Applications |
| RoHS: | Yes |
| Lead: | Wire Leads |
| AEC-Q200: | No |
| Notes: | Not For New Design, Please Check Possible Alternative Parts (AltPart). |

Dimensions

| | |
|-----------|---------------|
| L | 18mm MAX |
| H | 14.5mm MAX |
| T | 7.5mm MAX |
| S | 15mm +/-0.4mm |
| LL | 4mm NOM |
| F | 0.8mm NOM |

Specifications

| | |
|-------------------------------|---------------------------|
| Capacitance: | 0.068 uF |
| Capacitance Tolerance: | 10% |
| Voltage AC: | 220 VAC |
| Voltage DC: | 630 VDC, 488.3 VDC (100C) |
| Temperature Range: | -55/+100°C |
| Rated Temperature: | 85°C |
| Insulation Resistance: | 30 GOhms |
| Max dV/dt: | 25 V/us |

Packaging Specifications

| | |
|-------------------|-----------|
| Packaging: | Bulk, Bag |
|-------------------|-----------|

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

KEMET

a YAGEO company

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)