

## C330C102JDG5TA7317

 ${\it GoldMax\,300\,Comm\,COG\,HV,\,Ceramic,\,1000\,pF,\,5\%,\,1000\,VDC,\,COG,\,GoldMax,\,Commercial\,Standard,\,Lead\,Spacing\,=\,5.08mm}$ 



Click here for the 3D model.

Dimensions	
L	7.62mm MAX
Н	9.14mm MAX
Т	5.08mm MAX
S	5.08mm +/-0.78mm
НО	18mm MIN
F	0.51mm +0.1/-0.025mm

Packaging Specifications			
Packaging	Ammo		
Packaging Quantity	1500		

General Information			
Series	GoldMax 300 Comm COG HV		
Style	Radial		
Description GoldMax, Commercial Standard			
RoHS	Yes		
Termination	Tin		
Failure Rate	N/A		
AEC-Q200	No		
Halogen Free	Yes		

Specifications	
Capacitance	1000 pF
Measurement Condition	1 MHz 1.0Vrms
Capacitance Tolerance	5%
Voltage DC	1000 VDC
Dielectric Withstanding Voltage	1200 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	COG
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	30PPM/C, 1MHz 1.0Vrms
Dissipation Factor	0.1% 1 MHz 1.0Vrms
Aging Rate	0% Loss/Decade Hour
Insulation Resistance	100 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)