
## KEMET Part Number: ALC10S1102DF

(A526EH103M050S)



## ALC10S, Aluminum Electrolytic, 10,000 uF, 20%, 50 VDC, -40/+85°C



General Information	
Series:	ALC10S
Dielectric:	Aluminum Electrolytic
Description:	Audio Grade Snap-In
Features:	Audio Grade
RoHS:	Yes
Lead:	2 Pin
AEC-Q200:	No
Component Weight:	70 g
Notes:	Dimensions Include Sleeving.
Shelf Life:	156 Weeks

Dimensions		
D	35mm NOM	
L	50mm NOM	
S	10mm +/-0.1mm	
LL	6.3mm +/-1mm	
F	2mm +/-0.1mm	

Packaging Specifications	
Sleeving:	Yes
Packaging:	Bulk, Bag

Specifications		
Capacitance:	10,000 uF	
Capacitance Tolerance:	20%	
Voltage DC:	50 VDC	
Temperature Range:	-40/+85°C	
Rated Temperature:	85°C	
Life:	15000 Hrs	
Leakage Current:	3000 uA (5min 20°C)	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)