



Click [here](#) for the 3D model.

Dimensions

| | |
|----|----------------|
| D | 12.5mm MAX |
| L | 12mm MAX |
| S | 5mm +/-0.5mm |
| LL | 3.5mm +/-0.5mm |
| F | 0.6mm NOM |

Packaging Specifications

| | |
|--------------------|-------|
| Component Weight | 3.3 g |
| Packaging | Ammo |
| Packaging Quantity | 1600 |

General Information

| | |
|-------------|--|
| Series | SBCP-11HY |
| Style | Through-Hole |
| Description | Radial Leaded, Ferrite Power Inductors |
| Features | DC-DC Converters, Nickel-Zinc (NiZn) Ferrite Core |
| RoHS | Yes |
| Lead | Wire Leads |
| Core | Ferrite |
| Notes | Contains 4 Reels of 400 pieces each. Do Not Expose To Direct Sunlight. |

Specifications

| | |
|----------------------|------------|
| Inductance | 33 uH |
| Inductance Tolerance | 20% |
| Temperature Range | -20/+105°C |
| Shielded | No |
| Current | 2.3 Amps |
| DC Resistance | 0.07 Ohms |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)