


SPC7.3222J100K33TR12

Aliases (F127SL222J100V)

SPC/F127, Film, Double Metallized PPS, General Purpose, 2200 pF, 5%, 63 VAC, 100 VDC, 100 °C, 2824, 3mm



Note: '()' correspond to the letters used in the product bulletin

Click here for the 3D model.

Dimensions		
Chip Size	2824	
L	7.3mm +/-0.2mm	
W	6mm +/-0.2mm	
Т	3mm +/-0.2mm	
F	0.5mm NOM	

Packaging Specifications	
Packaging	T&R
Packaging Quantity	2500

General Information	
Series	SPC/F127
Dielectric	Double Metallized PPS
Style	SMD Chip
RoHS	Yes
AEC-Q200	No
Component Weight	0.472 g
Shelf Life	104 Weeks
MSL	2

Specifications	
Capacitance	2200 pF
Capacitance Tolerance	5%
Voltage AC	63 VAC
Voltage DC	100 VDC
Temperature Range	-55/+125°C
Rated Temperature	100°C
Dissipation Factor	0.15% 1kHz, 0.25% 10kHz, 0.5% 100kHz
Insulation Resistance	15 GOhms
Max dV/dt	800 V/us

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)