



Click [here](#) for the 3D model.

Dimensions

L	57.5mm +0.8/-0.7mm
H	65mm +0.3/-0.7mm
T	45mm +0.5/-0.7mm
S	52.5mm +/-0.4mm
S1	20.3mm +/-0.4mm
LL	6mm +0/-2mm
F	1.2mm +/-0.05mm

Packaging Specifications

Packaging	Bulk, Box
Packaging Quantity	18

General Information

Series	C4AF
Dielectric	Metallized Polypropylene
Style	Radial
Features	Harsh Environmental Conditions
RoHS	Yes
Lead	4 Wire Leads
Qualifications	AEC-Q200, IEC61071, EN61071, VDE0560
AEC-Q200	Yes
Component Weight	210.2 g
Miscellaneous	Rth = 7 C/W.

Specifications

Capacitance	22.5 uF
Capacitance Tolerance	10%
Voltage AC	400 VAC
Voltage DC	800 VDC
Temperature Range	-55/+105°C
Rated Temperature	85°C
Insulation Resistance	1.33 GOhms
Max dV/dt	61 V/us
Resistance	2 mOhms
Ripple Current	37.4 Amps Irms (MAX), 1372.5 Amps Ipkr
Inductance	19 nH (ESL)

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)