



Click [here](#) for the 3D model.

### Dimensions

L	32mm +0.5/-0.7mm
H	33mm +0.2/-0.7mm
T	18mm +0.6/-0.7mm
S	27.5mm +/-0.4mm
LL	6mm +0/-2mm
F	0.8mm +/-0.05mm

### Packaging Specifications

Packaging	Bulk, Box
Packaging Quantity	80

### General Information

Series	C4AQ-M
Dielectric	Metallized Polypropylene
Style	Radial
RoHS	Yes
Lead	Wire Leads
Qualifications	AEC-Q200, IEC61071, EN61071, VDE0560
AEC-Q200	Yes
Component Weight	28.2 g
Miscellaneous	Rth = 27 C/W.

### Specifications

Capacitance	3.7 uF
Capacitance Tolerance	5%
Voltage DC	1200 VDC
Temperature Range	-55/+105°C
Rated Temperature	85°C
Insulation Resistance	8.1 GOhms
Max dV/dt	90 V/us
Resistance	10 mOhms (10kHz 70C)
Ripple Current	9.9 Amps Irms (10kHz 70C), 333 Amps Ipk
Inductance	27 nH

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)