

R413I233000T1K

Aliases (4131233000T1K)

R41T, Film, Metallized Polypropylene, Automotive Safety, 0.033 uF, 10%, 300 VAC (Y2), 125°C, Lead Spacing = 15mm



Click here for the 3D model.

Dimensions	
L	18mm +0.3/-0.5mm
н	13.5mm +0.1/-0.5mm
т	7.5mm +0.2/-0.5mm
S	15mm +/-0.4mm
LL	4mm +2mm
F	0.6mm +/-0.05mm

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	1000

General Information	
Series	R41T
Dielectric	Metallized Polypropylene
Style	Radial
Features	Automotive Grade, EMI Safety
RoHS	Yes
Lead	Cut
Safety Class	Y2
Qualifications	AEC-Q200, ENEC, UL, cUL, CQC
AEC-Q200	Yes
THB Performance	Yes
Component Weight	2.1 g

Specifications				
Capacitance	0.033 uF			
Capacitance Tolerance	10%			
Voltage AC	300 VAC (Y2)			
Temperature Range	-40/+125°C			
Rated Temperature	125°C			
Dissipation Factor	0.3% 1kHz			
Insulation Resistance	100 GOhms			
Max dV/dt	600 V/us			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and w	
warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capa	
correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given grat	is, and we assume no
obligation or liability for the advice given or results obtained.	

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)