


SBCP-47HY152B

Aliases (UPIO47HY152B00)

KEMET, SBCP-47HY, Power, 1500 uH, 10%, 2.5mm



General Inform	ation
Series	SBCP-47HY
Style	Through-Hole
Description	Radial Leaded, Ferrite Power Inductors
Features	DC-DC Converters, Nickel-Zinc (NiZn) Ferrite Core
RoHS	Yes
Lead	Wire Leads
Core	Ferrite

Specifications				
Inductance	1500 uH			
Inductance Tolerance	10%			
Temperature Range	-20/+105°C			
Shielded	No			
Current	0.13 Amps			
DC Resistance	8 Ohms			

Click here for the 3D model.

Dimensions	
D	5mm MAX
L	7.5mm MAX
Н	18mm +2mm
S	2.5mm +/-0.5mm
LL	3.5mm +/-0.5mm
F	0.5mm NOM

D 1 1	<u> </u>	e
Packaging	Speci	tication
i acitaging	opeer	neation

Component Weight	490 mg
Packaging	Bulk
Packaging Quantity	6000

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)