



Click [here](#) for the 3D model.

### Dimensions

D	50mm MAX
H	28mm MAX
LL	3.5mm +/-0.5mm
S	44mm NOM
Wire Size	1.4mm

### Packaging Specifications

Packaging	Tray
Packaging Quantity	60
Component Weight	100 g

### General Information

Series	SCR Three Phase
Style	Through-Hole
Features	High Impedance, Space Saving
RoHS	Yes
Miscellaneous	70 (K) Temperature Rise Max.
Core	Mn-Zn Ferrite

### Specifications

Voltage AC	500 VAC/VDC
Voltage DC	500 VDC
Inductance	1.5 mH (10 kHz)
Current	13 A
Temperature Range	-25/+120°C
DC Resistance	9.2 mOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)