


VS-JV10A-K01

Aliases (USEVJV10AK0100)

KEMET, VS-J, Vibration, Metal Sealed, Piezoelectric, Propietary Piezo Ceramic Material, Built-in Amplifier, Detachable Cable



Click here for the 3D model.

Dimensions	
D	18mm NOM
L	29.4mm NOM
L2	22.4mm +/-0.5mm
Т	11mm +/-0.5mm

Packaging Specifications			
Packaging	Bulk, Box		
Packaging Quantity	10		
Component Weight	19 g		

General Information		
Series	VS-J	
Туре	Vibration	
Style	Metal Sealed	
Description	Vibration Sensor	
Features	Propietary Piezo Ceramic Material, Built-in Amplifier, Detachable Cable	
RoHS	With Exemptions	
REACH	SVHC (PZT - CAS 12626-81-2)	
SCIP Number	640fe643-8c06-4489-831d-d384ddba7405	

Specifications				
Temperature Range	-25/+85°C			
Power Supply Voltage	3.2 - 5.5 VDC			
Protection	IP67 and oil-resistant			
Sensitivity	10 mV/m/s²			
Frequency Range	10 - 15,000 Hz			
Measuring Range	+/-100 m/s²			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)