



Click [here](#) for the 3D model.

Dimensions

| | |
|----|-------------------|
| D | 8.89mm +/-0.51mm |
| L | 17.53mm +/-0.76mm |
| LL | 38.1mm MIN |
| F | 0.64mm +/-0.05mm |

Packaging Specifications

| | |
|--------------------|------------|
| Packaging | T&R, 305mm |
| Packaging Quantity | 300 |

General Information

| | |
|-------------------------|--|
| Series | LDD Mil X7R PRF39014 |
| RoHS | No |
| Prop 65 | ⚠ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov . |
| SCIP Number | 132e61c0-5a2b-4355-a818-8e6ea80949b5 |
| Termination | Lead (SnPb) |
| Testing and Reliability | MIL-PRF-39014 |
| Qualifications | MIL-PRF-39014 |
| AEC-Q200 | No |

Specifications

| | |
|---------------------------------|--------------|
| Capacitance | 3.3 uF |
| Capacitance Tolerance | 10% |
| Voltage DC | 50 VDC |
| Dielectric Withstanding Voltage | 125 VDC |
| Temperature Range | -55/+125°C |
| Temperature Coefficient | X7R |
| Dissipation Factor | 2.5% |
| Insulation Resistance | 303.03 MOhms |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)