



### Dimensions

|    |                    |
|----|--------------------|
| L  | 18mm +/-0.5mm      |
| H  | 14.5mm +0.1/-0.5mm |
| T  | 8.5mm +0.2/-0.5mm  |
| S  | 15mm +/-0.4mm      |
| LL | 25mm +2/-1mm       |
| F  | 0.6mm +/-0.05mm    |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 500       |

### General Information

|                 |                          |
|-----------------|--------------------------|
| Series          | R46 310 VAC 125C         |
| Dielectric      | Metallized Polypropylene |
| Style           | Radial                   |
| Features        | EMI Safety               |
| RoHS            | Yes                      |
| Lead            | Wire Leads               |
| Safety Class    | X2                       |
| Qualifications  | ENEC, UL, cUL, CQC       |
| AEC-Q200        | No                       |
| THB Performance | No                       |

### Specifications

|                       |              |
|-----------------------|--------------|
| Capacitance           | 0.33 uF      |
| Capacitance Tolerance | 10%          |
| Voltage AC            | 310 VAC (X2) |
| Voltage DC            | 630 VDC      |
| Temperature Range     | -40/+125°C   |
| Rated Temperature     | 125°C        |
| Dissipation Factor    | 0.2% 1KHz    |
| Insulation Resistance | 10 GOhms     |
| Max dV/dt             | 400 V/us     |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)