

KEMET Part Number: PHE840MD6470JD15R032
(F840DM474J275CL32JVBLK)

PHE840M/F840, Film, Metallized Polypropylene, Safety, 0.47 uF, 5%, 275 VAC (X2), 760 VDC, 105°C, Lead Spacing = 22.5mm



Dimensions

L	26mm MAX
H	18.5mm MAX
T	9mm MAX
S	22.5mm +/-0.4mm
LL	3.2mm NOM
F	0.8mm NOM

Packaging Specifications

Packaging:	Bulk, Bag
-------------------	-----------

General Information

Series:	PHE840M/F840
Dielectric:	Metallized Polypropylene
Style:	Radial
Features:	EMI Safety
RoHS:	Yes
Lead:	Wire Leads
Safety Class:	X2
Qualifications:	ENEC, UL, cUL
AEC-Q200:	No
THB Performance:	No
Notes:	Not For New Design, Please Check Possible Alternative Parts (AltPart).

Specifications

Capacitance:	0.47 uF
Capacitance Tolerance:	5%
Voltage AC:	275 VAC (X2)
Voltage DC:	760 VDC
Temperature Range:	-55/+105°C
Rated Temperature:	105°C
Dissipation Factor:	0.1% 1kHz, 0.4% 10kHz
Insulation Resistance:	21.2766 GOhms
Max dV/dt:	100 V/us

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)