

MMK22.5106K100D19L4TRAY

Aliases (F601DY106K100C, MMK22,5106K100D19L4TRAY)

MMK/F601, Film, Metallized Polyester, General Purpose, 10 uF, 10%, 100 VDC, 85°C, Lead Spacing = 22.5mm



Click [here](#) for the 3D model.

Dimensions

L	26mm MAX
H	24.5mm MAX
T	15.5mm MAX
S	22.5mm +/-0.4mm
LL	4mm NOM
F	0.8mm NOM

Packaging Specifications

Packaging	Tray
-----------	------

General Information

Series	MMK/F601
Dielectric	Metallized Polyester
Style	Radial
Features	DC Multipurpose Applications
RoHS	Yes
Lead	Wire Leads
AEC-Q200	No
Component Weight	12.68 g
Notes	Not For New Design, Please Check Possible Alternative Parts (AltPart).

Specifications

Capacitance	10 uF
Capacitance Tolerance	10%
Voltage AC	63 VAC
Voltage DC	100 VDC, 77.5 VDC (100C)
Temperature Range	-55/+100°C
Rated Temperature	85°C
Insulation Resistance	500 MOhms
Max dV/dt	5 V/us

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)