

## PHE426KF7330JR06L2

Aliases (F426FS335J400C, PHE426KF7330JF15R06L2)

PHE426/F426, Film, Metallized Polypropylene, General Purpose, 3.3 uF, 5%, 400 VDC, 85°C, Lead Spacing = 27.5mm



Click [here](#) for the 3D model.

### Dimensions

|    |                 |
|----|-----------------|
| L  | 31.5mm MAX      |
| H  | 29mm MAX        |
| T  | 19mm MAX        |
| S  | 27.5mm +/-0.4mm |
| LL | 6mm NOM         |
| F  | 0.8mm NOM       |

### Packaging Specifications

|                    |      |
|--------------------|------|
| Packaging          | Tray |
| Packaging Quantity | 117  |

### General Information

|                  |  |
|------------------|--|
| Series           | PHE426/F426  |
| Dielectric       | Metallized Polypropylene   |
| Style            | Radial   |
| Features         | Pulse  |
| RoHS             | Yes  |
| Lead             | Wire Leads   |
| AEC-Q200         | No   |
| Component Weight | 19.5 g   |
| Notes            | Not For New Design, Please Check Possible Alternative Parts (AltPart). |

### Specifications

|                       |                         |
|-----------------------|-------------------------|
| Capacitance           | 3.3 uF                  |
| Capacitance Tolerance | 5%                      |
| Voltage AC            | 220 VAC                 |
| Voltage DC            | 400 VDC, 296 VDC (105C) |
| Temperature Range     | -55/+105°C              |
| Rated Temperature     | 85°C                    |
| Dissipation Factor    | 0.1% 1kHz               |
| Insulation Resistance | 9.0909 GOhms            |
| Max dV/dt             | 90 V/us                 |
| Inductance            | 6 nH                    |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)