

R75H, Film, Metallized Polypropylene, Automotive Grade, 0.47 uF, 5%, 1000 VDC, 105°C, Lead Spacing = 27.5mm



| General Information | |
|---------------------|---|
| Series: | R75H |
| Dielectric: | Metallized Polypropylene |
| Style: | Radial |
| Features: | Automotive Grade, Pulse |
| RoHS: | Yes |
| Lead: | Wire Leads |
| Qualifications: | AEC-Q200 |
| AEC-Q200: | Yes |
| Miscellaneous: | Above 105C DC And AC Voltage Derating Is 1.25%/C. |

| Dimensions | |
|------------|------------------|
| L | 32mm +0.3/-0.7mm |
| H | 25mm +0.1/-0.7mm |
| T | 13mm +0.2/-0.7mm |
| S | 27.5mm +/-0.4mm |
| LL | 25mm +2/-1mm |
| F | 0.8mm +/-0.05mm |

| Packaging Specifications | |
|--------------------------|-----------|
| Packaging: | Bulk, Bag |
| Packaging Quantity: | 288 |

| Specifications | |
|------------------------|---|
| Capacitance: | 0.47 uF |
| Capacitance Tolerance: | 5% |
| Voltage AC: | 250 VAC |
| Voltage DC: | 1000 VDC |
| Temperature Range: | -55/+125°C |
| Rated Temperature: | 105°C |
| Dissipation Factor: | 0.05% 1kHz, 0.08% 10kHz |
| Insulation Resistance: | 63.8298 GOhms |
| Max dV/dt: | 350 V/us |
| Resistance: | 16.9 mOhms (100kHz) |
| Ripple Current: | 9.23 Amps (100kHz 90C), 165 Amps (Peak) |
| Inductance: | 18 nH |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)