



Click [here](#) for the 3D model.

| Dimensions | |
|------------|-------------------|
| L | 180mm MIN |
| W | 85mm MIN |
| H | 60mm MIN |
| L1 | 115mm MIN |
| W1 | 100mm MIN |
| W2 | 115mm MIN |
| Z | 19mm MIN |
| K | 6.5mm MIN |
| M (Earth) | Threaded Studs M6 |

| Packaging Specifications | |
|--------------------------|------|
| Packaging | Bulk |
| Packaging Quantity | 1 |

| General Information | |
|---------------------|------------------------------------|
| Series | FLLE2-AN |
| Style | Chassis Mount |
| Description | Single Phase Chassis Mount Filters |
| Features | Single Phase |
| Phase | Single-phase |
| RoHS | Yes |
| Terminal Type | Threaded Studs M6 |

| Specifications | |
|-------------------|------------|
| Voltage AC | 300 VAC |
| Rated Frequency | 50-60 Hz |
| Rated Current | 55 A |
| Rated Temperature | 40°C |
| Temperature Range | -25/+100°C |
| Climate Category | 25/100/21 |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)