
KEMET Part Number: PHE820ED6150KR17T1

(F720DH154K300P)



PHE820E/F720, Film, Metallized Polyester, Safety, 0.15 uF, 10%, 300 VAC (X2), 760 VDC, 100°C, Lead Spacing = 22.5mm



Dimensions	
L	26mm MAX
Н	16mm MAX
Т	8mm MAX
S	22.5mm +/-0.4mm
HO	18.5mm +/-0.5mm
F	0.8mm NOM
G	0.5mm NOM

Packaging Specifications		
Packaging:	T&R, Large	
Packaging Quantity:	500	

General Information	
Series:	PHE820E/F720
Dielectric:	Metallized Polyester
Style:	Radial
Features:	EMI Safety
RoHS:	Yes
Lead:	Wire Leads
Safety Class:	X2
Qualifications:	ENEC, UL, cUL
AEC-Q200:	No
THB Performance:	No
Miscellaneous:	SRF= 3.9 MHz.
Notes:	Not For New Design, Please Check Possible Alternative Parts (AltPart).

Specifications		
Capacitance:	0.15 uF	
Capacitance Tolerance:	10%	
Voltage AC:	300 VAC (X2)	
Voltage DC:	760 VDC	
Temperature Range:	-40/+100°C	
Rated Temperature:	100°C	
Dissipation Factor:	1% 1kHz	
Insulation Resistance:	30 GOhms	
Max dV/dt:	100 V/us	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)

>>点击查看相关商品