

**KEMET Part Number: C0603C391K5GALTU**  
(C0603C391K5GAL7867)

SMD Comm COG SnPb, Ceramic, 390 pF, 10%, 50 VDC, COG, SMD, MLCC, Ultra-Stable, Low Loss, Class I, 0603




**Dimensions**

| Chip Size | 0603             |
|-----------|------------------|
| L         | 1.6mm +/-0.15mm  |
| W         | 0.8mm +/-0.15mm  |
| T         | 0.8mm +/-0.07mm  |
| S         | 0.7mm MIN        |
| B         | 0.35mm +/-0.15mm |

**Packaging Specifications**

|                            |                        |
|----------------------------|------------------------|
| <b>Packaging:</b>          | T&R, 180mm, Paper Tape |
| <b>Packaging Quantity:</b> | 4000                   |

**General Information**

|                          |   |
|--------------------------|---|
| <b>Series:</b>           | SMD Comm COG SnPb   |
| <b>Style:</b>            | SMD Chip  |
| <b>Description:</b>      | SMD, MLCC, Ultra-Stable, Low Loss, Class I  |
| <b>Features:</b>         | Ultra-Stable, Low Loss, Class I   |
| <b>RoHS:</b>             | No  |
| <b>Prop 65:</b>          |  <b>WARNING:</b> Cancer and reproductive harm - <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a> . |
| <b>SCIP Number:</b>      | 5549986b-60cf-4a2a-afbb-4ad1d7a11dcb  |
| <b>Termination:</b>      | Lead (SnPb)   |
| <b>Marking:</b>          | No  |
| <b>AEC-Q200:</b>         | No  |
| <b>Component Weight:</b> | 3700 ug   |
| <b>Shelf Life:</b>       | 78 Weeks  |
| <b>MSL:</b>              | 1   |

**Specifications**

|  |                           |
|--|---------------------------|
| <b>Capacitance:</b>  | 390 pF                    |
| <b>Measurement Condition:</b>  | 1 MHz 1.0Vrms             |
| <b>Capacitance Tolerance:</b>  | 10%                       |
| <b>Voltage DC:</b>   | 50 VDC                    |
| <b>Dielectric Withstanding Voltage:</b>                                    | 125 VDC                   |
| <b>Temperature Range:</b>  | -55/+125°C                |
| <b>Temperature Coefficient:</b>  | COG                       |
| <b>Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC):</b> | 30 ppm/C, 1MegaHz 1.0Vrms |
| <b>Dissipation Factor:</b>   | 0.1% 1 MHz 1.0Vrms        |
| <b>Aging Rate:</b>   | 0% Loss/Decade Hour       |
| <b>Insulation Resistance:</b>  | 100 GOhms                 |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)