
KEMET Part Number: CAN19X823MAGACTU

(CAN19X823MAGAC7800)



CAN SMD Indust 250, Ceramic, 0.082 uF, 20%, C0G, SMD Chip, MLCC, AC Rated, 1825



			ierminati	ion:
		Marki	ing:	
			AEC-Q2	200:
			М	ISL:
		•		
Dimensions		Spo	ecifi	
	Chip Size	1825	Capacitar	nce:

Dimensions		
Chip Size	1825	
L	4.6mm +/-0.4mm	
W	6.4mm +/-0.4mm	
Т	2.5mm +/-0.20mm	
В	0.7mm +/-0.35mm	

Packaging Specifications		
Packaging:	T&R, 180mm, Paper Tape	
Packaging Quantity:	500	

Specifications	
Capacitance:	0.082 uF
Measurement Condition:	1 kHz 1.0Vrms
Capacitance Tolerance:	20%
Voltage AC:	250 VAC
Dielectric Withstanding Voltage:	945 VDC
Temperature Range:	-55/+125°C
Temperature Coefficient:	COG
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC):	15%, 1kHz 1.0Vrms
Dissipation Factor:	0.1% 1 kHz 1.0Vrms
Aging Rate:	0% Loss/Decade Hour
Insulation Resistance:	10 GOhms

General Information

CAN SMD Indust 250

Flexible Termination

SMD Chip, MLCC, AC Rated

Temperature Stable, Class I

SMD Chip

No No 1

Series:

Style:

Description:

Features:

RoHS:

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)