

## PHE426JA5470JR05

Aliases (F426AG473J300C, PHE426JA5470JA01R05)

PHE426/F426, Film, Metallized Polypropylene, General Purpose, 0.047 uF, 5%, 300 VDC, 85°C, Lead Spacing = 10mm



Click [here](#) for the 3D model.

### Dimensions

|    |               |
|----|---------------|
| L  | 13mm MAX      |
| H  | 9mm MAX       |
| T  | 4mm MAX       |
| S  | 10mm +/-0.4mm |
| LL | 5mm NOM       |
| F  | 0.6mm NOM     |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 1000      |

### General Information

|                  |  |
|------------------|--|
| Series           | PHE426/F426  |
| Dielectric       | Metallized Polypropylene   |
| Style            | Radial   |
| Features         | Pulse  |
| RoHS             | Yes  |
| Lead             | Wire Leads   |
| AEC-Q200         | No   |
| Component Weight | 0.571 g  |
| Notes            | Not For New Design, Please Check Possible Alternative Parts (AltPart). |

### Specifications

|                       |                          |
|-----------------------|--------------------------|
| Capacitance           | 0.047 uF                 |
| Capacitance Tolerance | 5%                       |
| Voltage AC            | 160 VAC                  |
| Voltage DC            | 300 VDC, 222 VDC (105C)  |
| Temperature Range     | -55/+105°C               |
| Rated Temperature     | 85°C                     |
| Dissipation Factor    | 0.05% 1kHz, 0.25% 100kHz |
| Insulation Resistance | 100 GOhms                |
| Max dV/dt             | 200 V/us                 |
| Inductance            | 6 nH                     |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)