


ESW337M035AG6AA

ESW, Aluminum Electrolytic, 330 uF, 20%, 35 VDC, -40/+105°C, Lead Spacing = 3.5mm



TERMINAL END VIEW



Click here for the 3D model.

Dimensions		
D	8mm +/-0.5mm	_
L	20mm +2mm	
S	3.5mm +/-0.5mm	
LL Negative	15mm MIN	
LL Positive	20mm MIN	
F	0.6mm NOM	

Packaging Specifications

Packaging	Bulk, Bag
Packaging Quantity	4000

General Information		
Series	ESW	
Dielectric	Aluminum Electrolytic	
Description	LowZ Single Ended Aluminum Electrolytic	
Features	Low Z	
RoHS	Yes	
Lead	Wire Leads	
AEC-Q200	No	

Specifications	,
Capacitance	330 uF
Capacitance Tolerance	20%
Voltage DC	35 VDC, 44 VDC (Surge)
Temperature Range	-40/+105°C
Rated Temperature	105°C
Life	4000 Hrs
Dissipation Factor	12%
Resistance	0.065 Ohms (100kHz)
Ripple Current	995 mAmps (100kHz 105C)
Leakage Current	115 uA (2min 20°C)
Impedance Ratio at -25C	2
Impedance Ratio at -40C	3

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)