



General Information		
Series	GF	
Style	Metal Box	
Description	Noise Filters	
RoHS	With Exemptions	
SCIP Number	d9c7b340-5c0a-4e16-b4ef-391381f88890	
Qualifications	UL	
Miscellaneous	30 K Self-Temperature Rise Max.	
Terminal Type	Screw	

Specifications		
Voltage AC	250 VAC	
Voltage	1500 VAC Withstanding Voltage 1 Min. Line to Ground	
Rated Current	5 A (AC/DC)	
Temperature Range	-20/+60°C	
Leakage Current	1 mA MAX (250 V 60 Hz)	
Resistance	300 MOhms MIN Insulation 500 VDC 1 Min. Line To Ground	

Click here for the 3D model.

Dimensions	
L	70mm NOM
W	53mm MAX
Н	29mm NOM

Packaging Specifications			
Packaging	Tray, Box		
Packaging Quantity	10		
Component Weight	130 g		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)