



Click [here](#) for the 3D model.

Dimensions

| | |
|----|------------------|
| L | 18mm +0.3/-0.5mm |
| H | 12mm +0.1/-0.5mm |
| T | 6mm +0.2/-0.5mm |
| S | 15mm +/-0.4mm |
| LL | 4mm +2mm |
| F | 0.8mm +/-0.05mm |

Packaging Specifications

| | |
|--------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 1750 |

General Information

| | |
|------------------|---------------------------------|
| Series | R76 |
| Dielectric | Double Metallized Polypropylene |
| Style | Radial |
| Features | Automotive Grade, Pulse |
| RoHS | Yes |
| Lead | Cut |
| Qualifications | AEC-Q200 |
| AEC-Q200 | Yes |
| Component Weight | 1.75 g |

Specifications

| | |
|-----------------------|--|
| Capacitance | 0.039 uF |
| Capacitance Tolerance | 10% |
| Voltage AC | 400 VAC |
| Voltage DC | 630 VDC |
| Temperature Range | -55/+110°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 0.03% 1kHz, 0.04% 10kHz, 0.1% 100kHz |
| Insulation Resistance | 100 GOhms |
| Max dV/dt | 3000 V/us |
| Resistance | 16.32 mOhms (100kHz) |
| Ripple Current | 4.7 Amps (100kHz 85C), 117 Amps (Peak) |
| Inductance | 10 nH |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)