

KEMET Part Number: R71VI3470CK10J
(71VI3470CK10J)

KEMET

a YAGEO company

R71, Film, Metallized Polypropylene, General Purpose, 0.47 uF, 5%, 520 VDC, 105°C, Lead Spacing = 15mm



General Information	
Series:	R71
Dielectric:	Metallized Polypropylene
Style:	Radial
Features:	PFC and Pulse
RoHS:	Yes
Lead:	Wire Leads
AEC-Q200:	No
Miscellaneous:	Above 105C DC And AC Voltage Derating Is 4%/C.

Dimensions	
L	18mm +/-0.5mm
H	18.5mm +0.1/-0.5mm
T	7.5mm +0.2/-0.5mm
S	15mm +/-0.4mm
H0	18.5mm +/-0.5mm
F	0.8mm +/-0.05mm

Packaging Specifications	
Packaging:	T&R, Large
Packaging Quantity:	800

Specifications	
Capacitance:	0.47 uF
Capacitance Tolerance:	5%
Voltage AC:	250 VAC
Voltage DC:	520 VDC
Temperature Range:	-40/+110°C
Rated Temperature:	105°C
Dissipation Factor:	0.1% 25C
Insulation Resistance:	63.8298 GOhms
Max dV/dt:	200 V/us
Resistance:	118.5 mOhms (100kHz)
Ripple Current:	1.28 Amps (100kHz 85C), 94 Amps (Peak)
Inductance:	10 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

KEMET

a YAGEO company

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)