

## ACR08D104KGS

ACR Indust COG HT200C, Ceramic, 0.1 uF, 10%, 100 VDC, COG, ACR Indust COG HT200C with C3 Technology, Radial, Lead Spacing = 10.16mm

### Dimensions

L	12.7mm MAX
W	12.7mm MAX
T	2.54mm MAX
S	10.16mm +/-0.76mm
LL	3.175mm MIN
F	0.635mm +/-0.051mm

### Packaging Specifications

Packaging	Waffle
Packaging Quantity	20

### General Information

Series	ACR Indust COG HT200C
Style	Radial
Description	ACR Indust COG HT200C with C3 Technology, Radial
Features	High Temperature
RoHS	No
Prop 65	<b>⚠ WARNING:</b> Cancer and reproductive harm - <a href="http://www.p65warnings.ca.gov">http://www.p65warnings.ca.gov</a> .
Termination	Gold
AEC-Q200	No
Shelf Life	72 Weeks

### Specifications

Capacitance	0.1 uF
Capacitance Tolerance	10%
Voltage DC	100 VDC
Dielectric Withstanding Voltage	150 VDC
Temperature Range	-55/+200°C
Temperature Coefficient	COG
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	30 ppm/C,1kHz 1.0Vrms
Dissipation Factor	0.15% 1 kHz 1.0Vrms
Insulation Resistance	10 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)