



Click [here](#) for the 3D model.

| Dimensions | |
|------------|------------------|
| L | 32mm +0.3/-0.7mm |
| H | 37mm +0.1/-0.7mm |
| T | 22mm +0.2/-0.7mm |
| S | 27.5mm +/-0.4mm |
| LL | 25mm +2/-1mm |
| F | 0.8mm +/-0.05mm |

| Packaging Specifications | |
|--------------------------|------|
| Packaging | Tray |
| Packaging Quantity | 112 |

| General Information | |
|---------------------|---------------------------------|
| Series | R76 |
| Dielectric | Double Metallized Polypropylene |
| Style | Radial |
| Features | Pulse |
| RoHS | Yes |
| Lead | Wire Leads |
| AEC-Q200 | No |

| Specifications | |
|-----------------------|---|
| Capacitance | 1.8 uF |
| Capacitance Tolerance | 5% |
| Voltage AC | 400 VAC |
| Voltage DC | 630 VDC |
| Temperature Range | -55/+110°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 0.04% 1kHz |
| Insulation Resistance | 16.66667 GOhms |
| Max dV/dt | 900 V/us |
| Resistance | 5.31 mOhms (100kHz) |
| Ripple Current | 13.48 Amps (100kHz 85C), 1620 Amps (Peak) |
| Inductance | 18 nH |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)