



Click [here](#) for the 3D model.

### Dimensions

|           |                |
|-----------|----------------|
| Footprint | 7343           |
| L         | 7.3mm +/-0.3mm |
| W         | 4.3mm +/-0.3mm |
| H         | 2.8mm +/-0.3mm |
| S         | 1.3mm +/-0.3mm |
| F         | 2.4mm +/-0.1mm |

### Packaging Specifications

|                    |            |
|--------------------|------------|
| Packaging          | T&R, 178mm |
| Packaging Quantity | 500        |

### General Information

|                  |  |
|------------------|--|
| Series           | T493 HRA   |
| Dielectric       | MnO <sub>2</sub> Tantalum  |
| Style            | SMD Chip   |
| Description      | SMD, MnO <sub>2</sub> , Molded, DLA Drawing  |
| RoHS             | No   |
| Prop 65          | <b>⚠ WARNING:</b> Cancer and reproductive harm - <a href="http://www.p65warnings.ca.gov">http://www.p65warnings.ca.gov</a> . |
| SCIP Number      | 652b281f-d242-4453-bc44-0655d646cec3   |
| Termination      | Hot Solder Dipped  |
| AEC-Q200         | No   |
| Component Weight | 412.33 mg  |

### Specifications

|                         |   |
|-------------------------|---|
| Capacitance             | 22 uF   |
| Capacitance Tolerance   | 10%   |
| Voltage DC              | 35 VDC (85C), 23.45 VDC (125C)                        |
| Temperature Range       | -55/+125°C  |
| Rated Temperature       | 85°C  |
| Dissipation Factor      | 6% 120Hz 25C  |
| Failure Rate            | B (0.1%/1000 Hrs)                                     |
| Resistance              | 0.4 Ohms (100kHz 25C)                                 |
| Leakage Current         | 7.7 uA (5min 25°C)                                    |
| Testing and Reliability | 10 Cycles Surge Current Testing At +25C After Weibull |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)