

KEMET Part Number: MMK7.5562M400K00L16.5TA16
(F601KE562M400Q, MMK7,5562M400K00L16,5TA16)



MMK/F601, Film, Metallized Polyester, General Purpose, 5600 pF, 20%, 400 VDC, 85°C, Lead Spacing = 7.5mm



| General Information | |
|---------------------|--|
| Series: | MMK/F601 |
| Dielectric: | Metallized Polyester |
| Style: | Radial |
| Features: | DC Multipurpose Applications |
| RoHS: | Yes |
| Lead: | Wire Leads |
| AEC-Q200: | No |
| Notes: | Not For New Design, Please Check Possible Alternative Parts (AltPart). |

| Dimensions | |
|------------|-------------------|
| L | 10mm MAX |
| H | 6mm MAX |
| T | 2.5mm MAX |
| S | 7.5mm +0.6/-0.1mm |
| H0 | 16mm NOM |
| F | 0.6mm NOM |

| Packaging Specifications | |
|--------------------------|-------------------------|
| Packaging: | Ammo, 330x330x50mm, Box |
| Packaging Quantity: | 5000 |

| Specifications | |
|------------------------|----------------------------------|
| Capacitance: | 5600 pF |
| Capacitance Tolerance: | 20% |
| Voltage AC: | 200 VAC |
| Voltage DC: | 400 VDC, 310 VDC (100C) |
| Temperature Range: | -55/+100°C |
| Rated Temperature: | 85°C |
| Dissipation Factor: | 0.8% 1kHz, 1.5% 10kHz, 3% 100kHz |
| Insulation Resistance: | 30 GOhms |
| Max dV/dt: | 40 V/us |
| Inductance: | 6 nH |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)