

**KEMET Part Number: C0603X471K2RACTU**  
(C0603X471K2RAC7867)

SMD Comm X7R Flex, Ceramic, 470 pF, 10%, 200 VDC, X7R, SMD, MLCC, FT-CAP, Temperature Stable, 0603



**Dimensions**

| Dimensions |                  |
|------------|------------------|
| Chip Size  | 0603             |
| L          | 1.6mm +/-0.17mm  |
| W          | 0.8mm +/-0.15mm  |
| T          | 0.8mm +/-0.15mm  |
| S          | 0.58mm MIN       |
| B          | 0.45mm +/-0.15mm |

**Packaging Specifications**

|                     |                        |
|---------------------|------------------------|
| Packaging:          | T&R, 180mm, Paper Tape |
| Packaging Quantity: | 4000                   |

**General Information**

|                   |                                       |
|-------------------|---------------------------------------|
| Series:           | SMD Comm X7R Flex                     |
| Style:            | SMD Chip                              |
| Description:      | SMD, MLCC, FT-CAP, Temperature Stable |
| Features:         | FT-CAP, Temperature Stable            |
| RoHS:             | Yes                                   |
| Termination:      | Flexible Termination                  |
| Marking:          | No                                    |
| AEC-Q200:         | No                                    |
| Component Weight: | 7300 ug                               |
| Shelf Life:       | 78 Weeks                              |
| MSL:              | 1                                     |

**Specifications**

|                                                                     |                                                 |
|---------------------------------------------------------------------|-------------------------------------------------|
| Capacitance:                                                        | 470 pF                                          |
| Measurement Condition:                                              | 1 kHz 1.0Vrms                                   |
| Capacitance Tolerance:                                              | 10%                                             |
| Voltage DC:                                                         | 200 VDC                                         |
| Dielectric Withstanding Voltage:                                    | 500 VDC                                         |
| Temperature Range:                                                  | -55/+125°C                                      |
| Temperature Coefficient:                                            | X7R                                             |
| Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC): | 15%, 1kHz 1.0Vrms                               |
| Dissipation Factor:                                                 | 2.5% 1 kHz 1.0Vrms                              |
| Aging Rate:                                                         | 3% Loss/Decade Hour: Referee Time is 1000 Hours |
| Insulation Resistance:                                              | 100 GOhms                                       |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)