



Click [here](#) for the 3D model.

Dimensions

L	31.5mm +0.5/-0.7mm
H	28mm +0.2/-0.7mm
T	14mm +0.3/-0.7mm
S	27.5mm +/-0.4mm
LL	6mm +0/-2mm
F	0.8mm +/-0.05mm

Packaging Specifications

Packaging	Bulk, Box
Packaging Quantity	96

General Information

Series	C4AQ-M
Dielectric	Metallized Polypropylene
Style	Radial
RoHS	Yes
Lead	Wire Leads
Qualifications	AEC-Q200, IEC61071, EN61071, VDE0560
AEC-Q200	Yes
Component Weight	18.6 g
Miscellaneous	Rth = 33 C/W.

Specifications

Capacitance	12.5 uF
Capacitance Tolerance	10%
Voltage DC	500 VDC
Temperature Range	-55/+105°C
Rated Temperature	85°C
Insulation Resistance	2.4 GOhms
Max dV/dt	65 V/us
Resistance	6.7 mOhms (10kHz 70C)
Ripple Current	11 Amps Irms (10kHz 70C), 813 Amps Ipk
Inductance	24 nH

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)