


KEMET Part Number: 10HS35B474K
(10HS35B474K)

HS RAD-LDD Space X7R HV, Ceramic, 0.47 uF, 10%, 1000 VDC, X7R, Lead Spacing = 29.84mm



Dimensions

L	31.75mm MAX
H	15.24mm MAX
T	6.89mm MAX
S	29.845mm +/-0.762mm
LL	31.75mm MIN
F	0.635mm NOM

Packaging Specifications

Packaging:	Bulk, Bag
Packaging Quantity:	1

General Information

Series:	HS RAD-LDD Space X7R HV
Style:	Radial
RoHS:	No
Prop 65:	WARNING: Cancer and reproductive harm - www.p65warnings.ca.gov .
SCIP Number:	2340ecb8-2b2f-4a8e-990d-e9ce728f4668
Termination:	Lead (SnPb)
Failure Rate:	N/A
AEC-Q200:	No

Specifications

Capacitance:	0.47 uF
Capacitance Tolerance:	10%
Voltage DC:	1000 VDC
Dielectric Withstanding Voltage:	1500 VDC
Temperature Range:	-55/+125°C
Temperature Coefficient:	X7R
Dissipation Factor:	2.5%
Insulation Resistance:	2.1 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)