


TRS1-90BPR001

Aliases (USEP90BPR00100)

KEMET, TRS-P, Thermal Reed Switch, Screw-In, 3C Temperature Accuracy, High Reliability, High-Speed Response, Long Operational Life, Excellent Environmental Durability, High Temperature Accuracy, 90°C, Break



	21. 5	> 31	4	Otyle	OCI C V
Epoxy Resin "Yellow"	_ 7_,	14 5. 5		Description	Therr
	9	9min. Seal F	1~2.5	Features	High I Oper High
				RoHS	Yes
\ \disp\{\tau\}	1	NIVY V	Soldering Lead Free		

Click here for the 3D model.

Dimensions		
L	31mm NOM	
W	14mm NOM	

Packaging Specifications	
Packaging Quantity	100
Component Weight	15 g

General Information		
Series	TRS-P	
Type	Thermal Reed Switch	
Style	Screw-In	
Description	Thermal Reed Switch	
Features	High Reliability, High-Speed Response, Long Operational Life, Excellent Environmental Durability, High Temperature Accuracy	
RoHS	Yes	

Specifications	
Switching Temperature	90C +/-3C
Temperature Range	-20/+130°C
Contact Type	Break
Voltage DC	100 VDC MAX (Opening/Closing)
Current	0.5 Amps DC MAX (Opening/Closing), 5 mAmps MIN (IVDC, Opening/Closing)
Resistance	500 mOhms MAX (Contact Resistance)
Max Opening/Closing Power	10 W (DC)
Max Opening/Closing Voltage	100 V (DC)
Differential Temperature	10C Maximum

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)