


KEMET Part Number: PME278RB5150MR19T1
(P278QJ153M440P)

KEMET

a YAGEO company

PME278/P278, Film, Metallized Paper, Safety, 0.015 uF, 20%, 440 VAC (X1), 1000 VDC, 110°C, Lead Spacing = 15.2mm



Dimensions	
L	18.5mm MAX
H	11.1mm MAX
T	5.5mm MAX
S	15.2mm +/-0.4mm
H0	18.5mm +/-0.5mm
F	0.8mm +/-0.05mm

Packaging Specifications	
Packaging:	T&R, Large

General Information	
Series:	PME278/P278
Dielectric:	Metallized Paper
Style:	Radial
Features:	EMI Safety
RoHS:	Yes
Lead:	Wire Leads
Safety Class:	X1
Qualifications:	ENEC
AEC-Q200:	No
THB Performance:	No
Construction:	Molded
Miscellaneous:	SRF= 13 MHz.
Notes:	Not For New Design, Please Use The New P278 Series @ 480 VAC.

Specifications	
Capacitance:	0.015 uF
Capacitance Tolerance:	20%
Voltage AC:	440 VAC (X1)
Voltage DC:	1000 VDC
Temperature Range:	-40/+110°C
Rated Temperature:	110°C
Dissipation Factor:	1.3% 1kHz
Insulation Resistance:	12 GOhms
Max dV/dt:	1400 V/us

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

KEMET

a YAGEO company

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)