


T493B475M010BH6420

T493 HRA, Tantalum, MnO2 Tantalum, HRA, 4.7 uF, 20%, 10 VDC, SMD, MnO2, Molded, High Reliability, B (0.1%/1000 Hrs), 1.5 Ohms, 3528, Height Max = 2 1mm



Click	here	for	the	3D	mode	ᆈ

Dimensions		
Footprint	3528	
L	3.5mm +/-0.2mm	
W	2.8mm +/-0.2mm	
Н	1.9mm +/-0.2mm	
Т	0.13mm REF	
S	0.8mm +/-0.3mm	
F	2.2mm +/-0.1mm	
Α	1.9mm MIN	
В	0.4mm +/-0.15mm	
E	2.2mm REF	
G	1.8mm REF	
Р	0.35mm MIN	
R	1mm REF	
Χ	0.1mm +/-0.1mm	

Packaging Specifications			
Packaging	T&R, 178mm		
Packaging Quantity	2000		

General Information				
T493 HRA				
MnO2 Tantalum				
SMD Chip				
SMD, MnO2, Molded, High Reliability				
High Reliability				
No				
▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.				
1dd2e1b8-26dd-4d52-927c-6f9d519011aa				
Solder Coated				
No				
102.3 mg				
P and R dimensions represents the minimum solderable area of the termination surface entirely below cutout (if one is present).				

4.7 uF
20%
10 VDC (85C), 6.7 VDC (125C)
-55/+125°C
85°C
6% 120Hz 25C
B (0.1%/1000 Hrs)
1.5 Ohms (100kHz 25C)
0.5 uA (5min 25°C)
10 Cycles Surge Current Testing At -55C And +85C Before Weibull

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)