


## L4010C1RONDWDT

Aliases (L4010C1RONDWDT)

KEMET, L-DWD, Power, 1 uH, 20%, 4010(1616)



Click [here](#) for the 3D model.

### Dimensions

L	4mm +/-0.2mm
W	4mm +/-0.2mm
T	1mm MAX
S	2.5mm +/-0.2mm
LL	1.1mm +/-0.2mm

### Packaging Specifications

Packaging	T&R
Packaging Quantity	5000

### General Information

Series	L-DWD
Style	SMD
Chip Size	4010(1616)
Description	Shielded, Surface Mount Inductor
Features	Low Profile
RoHS	Yes

### Specifications

Inductance	1 uH
Inductance Tolerance	20%
Temperature Range	-25/+120°C
Shielded	Yes
Current	1050 mAmps (MAX)
DC Resistance	0.1 Ohms
Self-Resonant Frequency	116 MHz

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)