


GR900 SMD Space, Ceramic, 2200 pF, 10%, 100 VDC, BX, N/A, 0805





Click	here	for	the	3D	mode	ı

Dimensions	
Chip Size	0805
L	2.03mm +/-0.38mm (0.08 in +/-0.015 in)
W	1.27mm +/-0.38mm (0.05 in +/-0.015 in)
Т	1.4mm MAX (0.055 in MAX)
В	0.51mm +/-0.25mm (0.02 in +/-0.01 in)

Packaging Specifications	,
Packaging	Bulk, Bag

GR900 SMD Space
SMD Chip
No
▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.
4848e250-8508-4d7b-8b2c-b2000a1148f1
Lead (SnPb)
N/A
Mil-PRF-123 Group A
MIL-PRF-123 Group A
No
78 Weeks
1

Specifications	
Capacitance	2200 pF
Capacitance Tolerance	10%
Voltage DC	100 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	BX

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)