

## ARR08B395JGS

ARR Indust X7R HT200C, Ceramic, 3.9 uF, 5%, 50 VDC, X7R, ARR Indust X7R HT200C with C3 Technology, Radial, Lead Spacing = 10.16mm

Dimensions	
L	12.7mm MAX
W	12.7mm MAX
Т	2.54mm MAX
S	10.16mm +/-0.76mm
LL	3.175mm MIN
F	0.635mm +/-0.051mm

Packaging Specifications				
Packaging	Waffle			
Packaging Quantity	20			

General Information		
Series	ARR Indust X7R HT200C	
Style	Radial	
Description	ARR Indust X7R HT200C with C3 Technology, Radial	
Features	High Temperature	
RoHS	No	
Prop 65	A WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.	
Termination	Gold	
AEC-Q200	No	
Shelf Life	72 Weeks	

Specifications	
Capacitance	3.9 uF
Capacitance Tolerance	5%
Voltage DC	50 VDC
Dielectric Withstanding Voltage	75 VDC
Temperature Range	-55/+200°C
Temperature Coefficient	X7R
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	15%1kHz 1.0Vrms
Dissipation Factor	2.5% 1 kHz 1.0Vrms
Insulation Resistance	256.4 MOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)