
## **KEMET Part Number: R73PW4150SE00K**

(73PW4150SE00K)



R73, Film, Film/Foil Polypropylene, General Purpose, 1.5 uF, 10%, 630 VDC, 85°C, Lead Spacing = 37.5mm



General Information			
Series:	R73		
Dielectric:	Film/Foil Polypropylene		
Style:	Radial		
Features:	Pulse		
RoHS:	Yes		
Lead:	Cut		
AEC-Q200:	No		
Miscellaneous:	Above 85C DC And AC Voltage Derating Is 1.25%/C.		

**Specifications** 

Max dV/dt:

Inductance:

3000 V/us

20 nH

Dimensions			
L	41.5mm +0.3/-0.7mm		
Н	44mm +0.1/-0.7mm		
Т	24mm +0.3/-0.7mm		
S	37.5mm +/-0.4mm		
LL	4mm +2mm		
F	1mm +/-0.05mm		

Dimensions			· · · · · · · · · · · · · · · · · · ·	
			Capacitance:	1.5 uF
L	41.5mm +0.3/-0.7mm		Capacitance Tolerance:	10%
Н	44mm +0.1/-0.7mm		Voltage AC:	300 VAC
т	T 24mm +0.3/-0.7mm			
·		Voltage DC:	630 VDC	
S	37.5mm +/-0.4mm			
			Temperature Range:	-55/+105°C
LL	4mm +2mm		Dated Tomporature	85°C
F 1mm +/-0.05mm	i	Rated Temperature:	85 C	
	1111111 +/-0.051111111		Dissipation Factor:	0.03% 1kHz
			Insulation Resistance:	20 GOhms
			modiation Resistance.	20 0011113

Packaging Specifications		
Packaging:	Tray	
Packaging Quantity:	108	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generat



## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)