

SMD Mil-Equiv X7R HV 49467, Ceramic, 4700 pF, 20%, 4000 VDC, X7R, Surface Mount Ceramic Capacitor, 3530



General Information	
Series:	SMD Mil-Equiv X7R HV 49467
Style:	SMD Chip
Description:	Surface Mount Ceramic Capacitor
RoHS:	No
Prop 65:	<b>WARNING:</b> Cancer and reproductive harm - <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a> .
Termination:	Silver
AEC-Q200:	No

Dimensions	
Chip Size	3530
L	8.89mm +/-0.76mm
W	7.62mm +/-0.76mm
T	5.59mm NOM
B	1.143mm +/-1.524mm

Specifications	
Capacitance:	4700 pF
Capacitance Tolerance:	20%
Voltage DC:	4000 VDC
Dielectric Withstanding Voltage:	4800 VDC
Temperature Range:	-55/+125°C
Temperature Coefficient:	X7R
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC):	30 ppm/C
Dissipation Factor:	2.5%
Aging Rate:	2% Loss/Decade Hour
Insulation Resistance:	100 GOhms

Packaging Specifications	
Packaging Quantity:	50

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)