




GTX-2060-Y03

KEMET, GTX, EMI/RFI Filters, Noise Suppression, 250 VAC, 560 VDC, 6 A, 75x44x25mm







Click here for the 3D model.

Dimensions	
L	75mm +/-1mm
W	44mm +/-1mm
Н	25mm +/-1mm
S	17.6mm NOM
L1	66.7mm +/-0.5mm
W1	35mm +/-0.5mm

Packaging Specifications	
Packaging Quantity	30
Component Weight	124 g

General Information				
Series	GTX			
Style	Plastic Box			
Description	EMI Filter, With Y Capacitor			
Phase	Single-phase			
RoHS	With Exemptions			
Qualifications	UL, cUL, TUV			
Tightening Torque	1.2 ~ 1.4N-m (Recommended)			
Line Terminal	14-4(JST)			
Line Terminal Width	12 Max.			
Earth Terminal	R5.5-4(JST)			
Earth Terminal Width	9.5 Max.			
Miscellaneous	60 K Self-Temperature Rise Max.			
Terminal Type	Screw			

Specifications	
Voltage AC	250 VAC
Voltage DC	560 VDC
Rated Current	6 A
Temperature Range	-25/+55°C
Leakage Current	0.75 mA (MAX)

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)