## KEMET Part Number: CAN06X121KAGACTU

(CAN06X121KAGAC7867)



## CAN SMD Indust 250, Ceramic, 120 pF, 10%, C0G, SMD Chip, MLCC, AC Rated, 0603



Dimensions		
Chip Size	0603	
L	1.6mm +/-0.17mm	
W	0.8mm +/-0.15mm	
Т	0.8mm +/-0.10mm	
S	0.58mm MIN	
В	0.45mm +/-0.15mm	

Packaging Specifications		
Packaging:	T&R, 180mm, Paper Tape	
Packaging Quantity:	4000	

General Information		
Series:	CAN SMD Indust 250	
Style:	SMD Chip	
Description:	SMD Chip, MLCC, AC Rated	
Features:	Temperature Stable, Class I	
RoHS:	Yes	
Termination:	Flexible Termination	
Marking:	No	
AEC-Q200:	No	
MSL:	1	

Specifications		
Capacitance:	120 pF	
Measurement Condition:	1 MHz 1.0Vrms	
Capacitance Tolerance:	10%	
Voltage AC:	250 VAC	
Dielectric Withstanding Voltage:	945 VDC	
Temperature Range:	-55/+125°C	
Temperature Coefficient:	COG	
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC):	15%, 1MegaHz 1.0Vrms	
Dissipation Factor:	0.1% 1 MHz 1.0Vrms	
Aging Rate:	0% Loss/Decade Hour	
Insulation Resistance:	10 GOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.





单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)