



TOP VIEW  
Single or Double Chip Stack



PROFILE VIEW  
Single Chip Stack



Click [here](#) for the 3D model.

### Dimensions

|   |                  |
|---|------------------|
| L | 3.5mm +/-0.3mm   |
| W | 2.6mm +/-0.3mm   |
| T | 3.35mm +/-0.10mm |
| B | 0.8mm +/-0.15mm  |

### Packaging Specifications

|                    |                          |
|--------------------|--------------------------|
| Packaging          | T&R, 180mm, Plastic Tape |
| Packaging Quantity | 600                      |

### General Information

|                  |  |
|------------------|--|
| Series           | KPS SMD Comm X7R SnPb  |
| Style            | Stacked Chip   |
| Description      | SMD, MLCC, Stacked, Single Chip, Temperature Stable  |
| Features         | Temperature Stable   |
| RoHS             | No   |
| Prop 65          | <b>⚠ WARNING:</b> Cancer and reproductive harm - <a href="http://www.p65warnings.ca.gov">http://www.p65warnings.ca.gov</a> . |
| SCIP Number      | 795b247e-78a9-405c-8728-223c2d9782a2   |
| Termination      | Lead (SnPb)  |
| AEC-Q200         | No   |
| Component Weight | 160 mg   |
| Chip Size        | 1210-1   |
| Shelf Life       | 78 Weeks   |
| MSL              | 1  |

### Specifications

|  |   |
|--|---|
| Capacitance  | 4.7 uF  |
| Measurement Condition  | 1 kHz 1.0Vrms                                   |
| Capacitance Tolerance  | 10%   |
| Voltage DC   | 16 VDC  |
| Dielectric Withstanding Voltage                                    | 40 VDC  |
| Temperature Range  | -55/+125°C                                      |
| Temperature Coefficient  | X7R   |
| Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC) | 15%, 1kHz 1.0Vrms                               |
| Dissipation Factor   | 3.5% 1 kHz 1.0Vrms                              |
| Aging Rate   | 3% Loss/Decade Hour: Referee Time is 1000 Hours |
| Insulation Resistance  | 106.4 MOhms                                     |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)