KEMET Part Number: R73QN2680SE30M

(73QN2680SE30M)



R73, Film, Film/Foil Polypropylene, Automotive Grade, 0.068 uF, 20%, 1000 VDC, 85°C, Lead Spacing = 22.5mm



Dimensions		
L	26.5mm +0.3/-0.5mm	
Н	20mm +0.1/-0.5mm	
Т	11mm +0.2/-0.5mm	
S	22.5mm +/-0.4mm	
LL	4mm +2mm	
F	0.8mm +/-0.05mm	

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	360	

General Information		
Series:	R73	
Dielectric:	Film/Foil Polypropylene	
Style:	Radial	
Features:	Automotive Grade, Pulse	
RoHS:	Yes	
Lead:	Wire Leads	
Qualifications:	AEC-Q200	
AEC-Q200:	Yes	
Miscellaneous:	Above 85C DC And AC Voltage Derating Is 1.25%/C.	

Specifications		
Capacitance:	0.068 uF	
Capacitance Tolerance:	20%	
Voltage AC:	400 VAC	
Voltage DC:	1000 VDC	
Temperature Range:	-55/+105°C	
Rated Temperature:	85°C	
Dissipation Factor:	0.03% 1kHz, 0.04% 10kHz, 0.1% 100kHz	
Insulation Resistance:	100 GOhms	
Max dV/dt:	11000 V/us	
Inductance:	18 nH	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)