
KEMET Part Number: R73RR32205000K

(73RR32205000K)



R73, Film, Film/Foil Polypropylene, General Purpose, 0.22 uF, 10%, 1250 VDC, 85°C, Lead Spacing = 27.5mm



General Information		
Series:	R73	
Dielectric:	Film/Foil Polypropylene	
Style:	Radial	
Features:	Pulse	
RoHS:	Yes	
Lead:	Wire Leads	
AEC-Q200:	No	
Miscellaneous:	Above 85C DC And AC Voltage Derating Is 1.25%/C.	

Inductance:

18 nH

Dimensions			
L	L 32mm +0.3/-0.7mm		
Н	37mm +0.1/-0.7mm		
Т	22mm +0.2/-0.7mm		
S	27.5mm +/-0.4mm		
LL	LL 25mm +2/-1mm		
F	0.8mm +/-0.05mm		

		Specifications		
vimensions			Opcomeations -	
			Capacitance:	0.22 uF
	32mm +0.3/-0.7mm		Capacitance Tolerance:	10%
	37mm +0.1/-0.7mm		Voltage AC:	450 VAC
	22mm +0.2/-0.7mm			
27.5mm +/-0.4mm 25mm +2/-1mm 0.8mm +/-0.05mm		Voltage DC:	1250 VDC	
	Temperature Range:	-55/+105°C		
		Rated Temperature:	85°C	
		Dissipation Factor:	0.03% 1kHz, 0.06% 10kHz	
			Insulation Resistance:	100 GOhms
	<u> </u>	1	Max dV/dt:	11000 V/us

Packaging Specifications		
Packaging:	Tray	
Packaging Quantity:	112	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)