



Click [here](#) for the 3D model.

Dimensions

| | |
|----|------------------|
| L | 32mm +0.5/-0.7mm |
| H | 22mm +0.3/-0.7mm |
| T | 13mm +0.3/-0.7mm |
| S | 27.5mm +/-0.4mm |
| LL | 25mm +2/-1mm |
| F | 0.8mm +/-0.05mm |

Packaging Specifications

| | |
|--------------------|-----|
| Packaging Quantity | 288 |
|--------------------|-----|

General Information

| | |
|-----------------|------------------------------|
| Series | R53 X2 310 VAC |
| Dielectric | Metallized Polypropylene |
| Style | Radial |
| Features | Automotive Grade, EMI Safety |
| RoHS | Yes |
| Lead | Wire Leads |
| Safety Class | X2 |
| Qualifications | ENEC, UL, cUL, CQC, AEC-Q200 |
| AEC-Q200 | Yes |
| THB Performance | Yes |

Specifications

| | |
|-----------------------|-----------------|
| Capacitance | 2.2 uF |
| Capacitance Tolerance | 20% |
| Voltage AC | 310 VAC (X2) |
| Voltage DC | 630 VDC |
| Temperature Range | -40/+110°C |
| Rated Temperature | 110°C |
| Dissipation Factor | 0.2% 1KHz |
| Insulation Resistance | 13.636364 GOhms |
| Max dV/dt | 150 V/us |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)