

SMD Mil-Equiv X7R HV 49467, Ceramic, 0.33 uF, 10%, 1000 VDC, X7R, 3333



Dimensions	
Chip Size	3333
L	8.382mm +/-0.762mm
W	8.382mm +0.381/-0.762mm
T	5.588mm MAX
B	1.143mm +/-0.381mm

Packaging Specifications	
Packaging:	Waffle
Packaging Quantity:	1

General Information	
Series:	SMD Mil-Equiv X7R HV 49467
Style:	SMD Chip
RoHS:	No
Prop 65:	WARNING: Cancer and reproductive harm - www.p65warnings.ca.gov .
Termination:	Lead (SnPb)
Failure Rate:	N/A
Testing and Reliability:	MIL-PRF-49467 Group A
Qualifications:	MIL-PRF-49467 Group A
AEC-Q200:	No
Miscellaneous:	Similar to Mil-PRF-49467; Group A testing excluding corona.
Shelf Life:	78 Weeks
MSL:	1

Specifications	
Capacitance:	0.33 uF
Capacitance Tolerance:	10%
Voltage DC:	1000 VDC
Dielectric Withstanding Voltage:	1500 VDC
Temperature Range:	-55/+125°C
Temperature Coefficient:	X7R
Insulation Resistance:	3 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)