


## SSRH24NH-30145

Aliases (UALS24H3014500)

KEMET, SSRH24NV/NH, AC Line Filters, Common Mode, 14.5 mH



Click here for the 3D model.

Dimensions	
L	25.5mm MAX
T	25.5mm MAX
Н	18mm MAX
LL	3.5mm +/-0.5mm
S	13mm NOM
S1	21mm NOM
Wire Size	0.6mm

Packaging Specifications	
Packaging	Tray
Packaging Quantity	300
Component Weight	22.5 g

General Information		
Series	SSRH24NV/NH	
Style	Through-Hole	
Features	Compact Size, Light Weight, Low Rdc, Ultra-High Impedance	
RoHS	Yes	
Miscellaneous	65 (K) Temperature Rise Max.	
Core	Mn-Zn Ferrite	

Specifications	
Voltage AC	250 VAC
Inductance	14.5 mH (10 kHz)
Current	3 A
Temperature Range	-25/+120°C
DC Resistance	102 mOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)